

INTRODUCTION

An important update to the Department of Defense Instruction 6055.12, "Hearing Conservation Program" was published and effective on Nov. 22, 2023. The significant change to the instruction is a new requirement calling for hearing protector fit testing to be conducted for all DOD personnel who have documented noise exposure greater than or equal to 95dBA 8-hour time weighted average (TWA) and who are enrolled in a service hearing conservation program (HCP).

WHAT IS HEARING PROTECTOR FIT TESTING?

Hearing protector fit testing is a procedure used to quantitatively measure the amount of noise reduction a specific hearing protector is providing a user. Fit testing measures the personal attenuation rating (PAR) specific to each individual ear and hearing protector. The PAR is a real-world measurement of the overall attenuation the hearing protector provides the individual's ear.

WHY DO FIT TESTING?

- Identify workers at risk for noise-induced hearing loss due to inadequate hearing protector fit
- Properly select worker's hearing protectors to meet individual and environmental needs
- "Train-the-trainer" to better match hearing protectors to meet individual worker needs
- Train workers to properly fit and use hearing protectors
- Increase self-efficacy among workers who must wear hearing protectors
- Improve training outcomes by providing real-time feedback and documentation
- Motivate workers to consistently use hearing protectors in noisy environments
- Comply with federal regulations and service-specific policy requirements for fitting hearing protectors, providing training, and maintaining records
- Evaluate hearing conservation program effectiveness
- Reduce noise-induced hearing loss for those enrolled in DOD HCPs

"Fit-testing is an effective, practical, and essential tool for preventing occupational hearing loss." (CDC, 2018)

"The most accurate procedure(s) for checking the fit of an earplug by measuring real-world attenuation." (CAOHC, 2014)

"Fit testing, which is a better indicator of individual performance, can be used to determine if the employee is not achieving adequate protection and remedy the problem via training or selection of an alternative hearing protection device." (AIHA, 2022).



WHO WILL RECEIVE FIT-TESTING AND WHEN?

- (1) All DOD personnel enrolled in their service HCP and exposed at or above 95 dBA 8-hour TWA will have a hearing protector fit-test at the initial reference audiogram or prior to initial duty in hazardous noise areas or as soon as possible after employment begins.
- (2) When a positive Significant Threshold Shift (STS) is identified on the periodic audiogram. A hearing protector fit test will be used to evaluate the hearing protection devices, confirm adequacy of fit, and PAR for the noise environment.
- (3) When physical changes to a person's ear canal cause poor fit of assigned hearing protection devices.
- (4) If the primary type of fitted hearing protection device is no longer available (e.g. employee switches from earplugs to ear muffs).
- (5) When a single frequency 15 dB shift at 1000, 2000, 3000, and 4000 Hz occurs.

*Note: These are the minimum requirements for hearing protector fit-testing in the DOD—services may institute more stringent requirements for hearing protector fit-testing to better meet the needs of their respective HCP.

REFERENCES AND RESOURCES

Best practice bulletin: Hearing protection-Emerging Trends: Individual Fit Testing (2008, May 13). Retrieved July 8, 2022, from http://www.hearingconservation.org/assets/docs/AllianceRecommendationForFitTesting_Final.pdf

Centers for Disease Control and Prevention. (2018, February 6). CDC - noise and hearing loss prevention - HPD well-FIT™ - NIOSH workplace safety and health topic. Centers for Disease Control and Prevention. Retrieved July 26, 2022, from <https://www.cdc.gov/niosh/topics/noise/reducenoiseexposure/hpdwell-fit.html>

Department of Labor Logo United States Department of Labor. Occupational Noise Exposure - Hearing Conservation Program | Occupational Safety and Health Administration. (n.d.). Retrieved July 8, 2022, from <https://www.osha.gov/noise/hearing-programs>

DOD Instruction 6055.12 Hearing Conservation Program. (2019, August 14). Retrieved July 8, 2022, from <https://www.esd.whs.mil/Portals/54/Documents/DD/issuances/dodi/605512p.pdf>

Federman, J., & Duhon, C. (2016). The viability of hearing protection device fit-testing at Navy and Marine Corps Accession Points. *Noise and Health*, 18(85), 303–311. <https://doi.org/10.4103/1463-1741.195806>

Federman, J., Karch, S. J., & Duhon, C. (2020). How hearing conservation training format impacts personal attenuation ratings in U.S. Marine Corps training recruits. *International Journal of Audiology*, 60(2), 151–159. <https://doi.org/10.1080/14992027.2020.1811407>

Hutchinson, T.L., & Schulz, T.Y. (2014). *Hearing conservation manual* (5th ed.). Council for Accreditation in Occupational Hearing Conservation

Gong, W., Liu, X., Liu, Y., & Li, L. (2019). Evaluating the effect of training along with fit testing on foam earplug users in four factories in China. *International Journal of Audiology*, 58(5), 269–277. <https://doi.org/10.1080/14992027.2018.1563307>

Liu, Y., Gong, W., Liu, X., & Li, L. (2019). Evaluating the effect of training along with fit testing on premolded earplug users in a Chinese petrochemical plant. *Ear & Hearing*, 41(4), 838–846. <https://doi.org/10.1097/aud.0000000000000803>

Meinke, D. K., Berger, E. H., Discoll, D. P., Neitzel, R. L., & Bright, K. (2022). *The Noise Manual* (6th ed.). American Industrial Hygiene Association.

Murphy, W. J., Themann, C. L., & Murata, T. K. (2016). Hearing protector fit testing with off-shore oil-rig inspectors in Louisiana and Texas. *International Journal of Audiology*, 55(11), 688–698. <https://doi.org/10.1080/14992027.2016.1204470>

DHA Hearing Center of Excellence contact:

Theresa Schulz, PhD

Please submit your questions to:

<https://health.mil/About-MHS/Contact-Us>

